



Seit 1872

Resistance
grade
CEN VIII

STACKE

S I C H E R H E I T M I T S Y S T E M

Euroline strongroom doors

for strongrooms in modular
and cast in situ design



STACKE is a leading manufacturer offering project planning, production and performance of constructional measures for strongrooms in modular design and traditional strongrooms cast in situ.

The room also comprises the strongroom or safe door tested and certified to the respective resistance grade. STACKE supplies strongroom doors of resistance grades II-XIII in accordance with EN 1143-1 and thus covers the total range of all resistance grades in a rather unique way.

This documentation provides information about strongroom doors of the resistance grade CEN VIII. The table with the heading "Technical Data" is a short version of the performance description giving the major data.


The installation drawing - an example of resistance grade VIII - relates to the installation in walls cast in situ. Detailed drawings - by model and resistance grade - are available on request.

For room systems made of prefabricated elements in modular design, the door and the frame are integrated in the prefabricated walls.

STACKE safe doors in strongrooms can be used wherever valuables are to be securely stored and locked away. This includes applications in industry, trade, pharmaceutical companies, security transportation companies, authorities and private households. Thanks to the wide range of products, the demands of private persons and those of large and national banks can be satisfied equally well. Please feel free to contact us.

Euroline strongroom doors

Resistance grade
CEN VIII



Installation drawing

For walls cast in situ to resistance grade VIII in accordance with EN 1143-1.

Technical data		EL WT 170 VIII
Resistance grade to EN 1143-1:		VIII
Certificate:		VdS
Door opening dimensions:		1980 x 900 mm
Door thickness:		170 mm
Compact thickness before the locking system:		100 mm
Weight:		approx. 1.030 kg
Door case for wall cast in situ, optional, at extra cost:		430 mm
Pivot point of door, optionally R or L:		x
Lock with 3 strike plates à 400 mm, with blue zinc coating:		x
Hinge securing profile over total door height:		x
Lock weld, external, in addition to the lock:		7
Cable channel via central door hinge, invisible:		x
Lock encasing lock: Cylindrical lever lock:		x
Equipped for use with an IAS, without IAS components:		x
Lock: (Standard)		1/KL+1/CL Class 3
Lock: (Option)	mechanical:	---
Lock: (Option)	electronic:	1/KL+1/ECL TwinLock Cl. 3
		2/ECL TwinLock Cl. 3

KL=key lock, CL=mechanical code lock, ECL=electronic code lock

Stacke GmbH
Jülicher Str. 390/392 · D-52070 Aachen
Telephone 0049 (0)241 16808-0
Telefax 0049 (0)241 16808-30
info@stacke-safe.de · www.stacke-safe.de

STACKE