

STACKE Info

BRIEF UP TO DATE INFORMATION ON NEW PRODUCTS

EL 80 C MS

The Euroline safe with fold-in door

as a 24-hour box
for a staff-operated automated unit at cash desks
(MULTISAFE/SAFEMASTER or similar units),
resistance grade III
VdS-tested and certified according to EN 1143-2
ECB S-Euro certified according to EN 1143-2

The compact design allows easy integration into the customer desk area or the direct environment of the staff. The safe door smartly disappears beside the safe body nearly without application of force. The cash safe itself is moved forward using special kinematics until it is flush with the front side of the safe.

The safe system is used for the secure storage of valuables during the lunch break and during the night. The lock standard with mechanical code lock and key lock allows opening it in accordance with the double check principle. The opening philosophy can be adapted to the operator's concept by means of different optionally equipped electronic locks.

Technical data

Outside dimensions:	800 x 574/879* x 852/870* mm (hxwxd)
Inside dimensions:	700 x 474 x 670 mm (hxwxd)
Clear:	430 mm (w)
Armature:	+ 40 mm outside (d)
* Total outside dimensions incl. facing for slide-in	
Pivot point of the door:	DIN right, single-leaf fold-in door
Anchoring:	4-fold, pre-equipped for (but without) tear-off detector
IAS:	Pre-equipment according to VdS, but without the IAS components
Weight:	approx. 430 kg (without fittings)
Special equipment:	Potential equalization, junction box, plug with terminals, cold-device socket, hard-wired, flexible cable routing between door and junction box



Stacke GmbH • Jülicher Straße 390/392 • D 52070 Aachen
Telefon: 0049 (0)241 16808-0
Telefax: 0049 (0)241 16808-30
info@stacke-safe.de • www.stacke-safe.de

STACKE